Command Center



Every Jet Commercial Wastewater Treatment Plant is supplied with a pre-wired electrical control panel that can monitor motor and blower operations, flow, chlorination, spray, pumps and other auxiliary equipment.

All Jet Commercial Plant electrical control equipment is monitored here, at the control panel. That equipment is pre-wired at the Jet factory. All switches and controls are clearly identified, and a wiring diagram is furnished with each panel. Before shipment of any control panel, Jet fully tests all mechanical and electrical equipment to make certain that all components are operating properly.

An optional 24-hour time clock permits automatic cycling of the motor(s) and blower(s). This clock is preset at the Jet factory to operate the motor(s), blower(s) and foam control for 15 minutes of each half hour. Motors and blowers can be run manually with the toggle switch that is included.

In our 2000 Series plants, the motor, blowers and the control panel itself are protected inside a Jet weatherproof fiberglass equipment housing. In Jet Series 3000 plants, a

separate weatherproof sheet metal enclosure with an equivalent NEMA 3R rating houses all electrical controls. This enclosure is protected with at least two coats of weather resistant paint. Both 2000 and 3000 Series enclosures are secured with master-keyed padlocks.



Commercial Plants

Control Panel Options:

- 24-Hour Time Clock
- Flow Recorder
- Test Switch
- 7-Day Time Clock
- 115 V Receptacle
- Foam Control/Spray Option
- Chlorinator Option
- Comminutor Option
- Spare Switch
- Automatic Alternation

Do It Right The First Time:

buy a Jet



Fax 440.442.9008 • email@jetincorp.com • www.jetincorp.com